1

Description

Selection of the user language on a purely acoustically controlled telephone

In communication and information equipment, text information
is displayed in the language specified by the country version.
Accompanying this, there is the facility for the user to set
the language required as the user language or operator
language. If - for whatever reason - the language of the user
interface is now altered, the user faces the problem of
resetting the user language required without the option of
being guided to the relevant menu entry or control status by
feedback in text form.

This problem is a general one and is not restricted to
graphical user interfaces with keyboard or mouse input. On the
contrary, there will in future be more and more terminal
devices which are operated purely acoustically. The problem is
also faced at call centers which are operated purely
acoustically. Here, speech input is effected via speech
recognition and speech output either through the playing of
preproduced speech recordings or through automated speech
synthesis in the form of a text-to-speech conversion.

In devices with a screen input or display input and keyboard
input, the following procedure is found for solving the
problem shown: in general, there is the facility for resetting
the device to the factory language setting. This is usually
carried out by means of a defined key combination. There are
also devices in which a language menu can be activated in a
simple manner, the user being able to select the target
language. This then looks approximately as follows:

Deutsch
Français
English
Українець (Ukrainian)
Românesc (Romanian)
...

Table 1

In this menu, the user can now select the required user language to be set. Such a procedure is of course not possible for purely acoustically controlled devices.

From this starting point, the object of the invention is to enable the selection of the user language of a device by means of a purely acoustic method. The selection facility is also designed to be available in particular in cases where the device cannot, or is not intended to, provide assistance through a display.

This object is achieved in the inventions specified in the independent claims. Advantageous embodiments will emerge from the sub-claims. By means of the invention, the user language to be set for a device can easily be set, simply by speaking the user language to be set in order to select the user language. An English person therefore says "English", a German person simply says "Deutsch", a Frenchman says "Français" and a Ukrainian says "Ukrajins'kyj" (English transliteration of "Ukrainian" in Polish script).

The implementation of this functionality in the speech

recognition means of the device is no trivial matter, which is why preferred options will be described in greater detail below.

One option consists in training a single-word recognizer to recognize the designations of the user languages which can be set. Since the algorithms used here are chiefly based on a simple pattern comparison, a sufficient number of speech recordings in which the speech of mother-tongue speakers is recorded in relation to the relevant language is needed for the training. A dynamic-time-warp (DTW) recognizer, in particular, can be used for this.

If the device should already have phoneme-based speech recognition, for example for other functionalities, then it is advantageous to employ this for setting the user language. There are three options for doing this.

For example, a multilingual Hidden Markov Model (HMM) which models the phonemes of all the languages can be used in the speech recognition means. A standardized representation of a phonetic alphabet, for example in the form of SAMPA phonemes, is particularly advantageous for this purpose.

As convincing as this approach is for the problem definition outlined, multilingual speech recognition means have in practice shown themselves to be inferior to language-specific modeling in terms of their recognition rate. A further acoustic model, which would use up further memory space, would therefore be needed for normal speech recognition in the device.

A different option, in which the phoneme sequences from the

HMMs, which phoneme sequences are associated with the designations of the user languages to be set, are combined for the different languages, therefore proves to be advantageous. It must, however, be borne in mind here that the degrees of match which the speech recognition system delivers for the words modeled in different phoneme inventories are not directly comparable with one another. This problem can be circumvented if, in the combined HMM, the degrees of match for the phoneme sequences from the different recognizable user languages are scaled.

A particularly clever option is produced if, instead of one multilingual HMM or the combination of phoneme sequences of several language-specific HMMs, only one single language-specific or country-specific HMM is used and at the same time the designations of the foreign user languages are modeled using the language-specific phoneme set. The example below for German, which is based on the menu in Table 1, serves as an explanation of this. The word models are in "phonetic" orthography:

| / d eu t sh. / |
| / f r o ng s ae / |
| /i ng l i sh / |
| /u k r ai n sk i j / |
| / r o m a n e sh t sh / |

Table 2

Here, the need to use a multilingual HMM or to combine phoneme sequences having different phoneme inventories in the recognition process does not apply.

In accordance with the introductory definition of the problem,

the device is in particular a mobile terminal in the form of a
mobile or cordless telephone, a headset or the server of a
call center.

Preferred embodiments of the method according to the invention
will emerge in the same way as the preferred embodiments of
the inventive device shown.

Further essential features and advantages of the invention
will emerge from the description of an embodiment with
reference to the drawing in which:

Figure 1   shows the procedure for setting the user
                language.

The device can be implemented in the form of a cordless
headset which is controlled exclusively via speech. This may
for example be a headset which establishes, with or without
cable, a connection to a base via Bluetooth, Dect, GSM, UMTS,
GAP or another transmission standard.

The headset has an on/off button and a so-called "P2T" (push-
to-talk) button, by means of which the audio channel is
switched for a defined time window to the speech recognition
means. The command control of the headset includes the brief
pressing of the P2T button, an acknowledgment of the pressing
of the button by a short beep and the subsequent speaking of
the required command, to which the device responds
accordingly.

When the device is first switched on (step 1) or after
resetting of the device (step 2), which is caused, for
example, by holding down the P2T button for a longer period,

the user initially finds him-/herself at the user-language
selection stage. This is communicated to the user by an
acoustic signal (step 3) which consists, for example, of a
longer beep or a multilingual request to speak the user
language to be set.

The user then speaks into the device, in the language to be
set, the designation of the language to be set (step 4). The
speech recognition means of the device then recognizes the
designation of the user language to be set spoken in the user
language to be set, provided that the user language to be set
is one of the several user languages settable for the device.
The user language setting means of the device then sets the
user language of the device to the user language recognized by
the speech recognition means, as a result of which the device
is initialized appropriately. The device can then be operated
(step 6) as if it had been switched on normally (step 5).

Tried and tested means and methods from the prior art can be
used to correct speech recognition and operating errors.

All the embodiments of the invention share the outstanding
advantage that they significantly simplify and speed up
operation of the device. Furthermore, where phoneme-based
recognition is used, there is no need for speech recordings to
be stored in the device. Optimal use is made here of the fact
that phoneme-based acoustic resources are already present in
the device.